

Model 5920 Moisture Analyzer

FEATURES

- Quartz-crystal technology provides accuracy, speed, and calibration stability
- On-line zero-gas verification confirms analytical stability
- Intuitive, easy-to-use interface with keypad and display allows access to operating variables
- Rack-mount design makes the analyzer ideal for analytical carts
- Menu-driven gas selection eliminates all manual adjustments

Building upon the success of our quartz-crystal moisture measurement technology, AMETEK's Model 5920 is an easy-to-use process moisture analyzer that offers a truly remarkable combination of performance features: multi-gas compatibility, exceptional accuracy, on-line verification, fast response speed, and wide measurement range.

The 5920 is ideal for critical moisture measurement applications including high purity gas production and semiconductor gases. Equipped with an on-line verification system, this state-of-the-art analyzer is designed to rapidly build and maintain operator confidence in its analyses. The verification system allows you to challenge the analyzer's sensor at will using a zero gas to check its baseline stability to confirm the sensor's stability and sensitivity to low ppbv moisture concentrations.

SUPERIOR PERFORMANCE

Multi-gas compatibility

The Model 5920 combines the excellent multi-gas compatibility of the proven Model 5900 with a new, easy-to-use operator interface. A single, simple menu selection is all that is needed to re-configure the 5920 for a new gas type. There are no other necessary adjustments on the analyzer.



Model 5920 Moisture Analyzer

So, if you want to analyze industrial, high purity, or semiconductor grade gases and need an instrument that is compatible with virtually all bulk, ultra-high purity gases including inerts (He, Ar, Ne, Xe, Kr), H₂, O₂, and N₂, turn to the Model 5920.

Exceptional accuracy

The Model 5920 is perfect for moisture applications that require stable and accurate results. The accuracy of this analyzer, ± 1 ppbv or $\pm 10\%$ of reading, is exceptional. Quartz-crystal technology and an on-line verification system combine to constantly provide assurance that the analyzer is continuing to provide you with this superior level of performance.

On-line zero-gas verification confirms analytical stability

The on-line verification system in the 5920 uses an internal zero verification system. The zero verification system strips the moisture from the sample gas prior to analysis by the sensor. This allows you to verify the zero point of the sensor's calibration enhancing accuracy and confidence in ppbv measurements. This system is

entirely internal to the analyzer eliminating the need to break process connections along with the "wet-up" that would occur from ambient moisture. An alarm contact alerts the operator if the analyzer fails verification. The verification sequences can be started on a programmable schedule or on manual demand.

Fast response speed

The Model 5920 responds quickly to both increases and decreases in moisture concentration because the analyzer employs a unique non-equilibrium measurement technique. This technique continuously exposes the sensor to wet sample gas followed by dry sample gas to make its analysis. With this technique, the analyzer never needs to wait for the sensor to reach equilibrium to establish its accurate measurement. Importantly, this technique is based upon the defined, repeatable physical properties of moisture transport to/from the sensor's surface. This means that quartz-crystal technology *never* consumes gross quantities of valuable gas nor does it employ questionable prediction software as is often used to "speed-up" the apparent response speeds of other, more limited technologies.

AMETEK's unique technique makes possible accurate moisture readings far faster than would be possible under equilibrium, or continuous, operating conditions.

Wide measurement range

The Model 5920 accurately measures from 1 ppbv to 150 ppbv. While this is the recommended operating range, the analyzer will provide trend indication up to 1000 ppbv so that you can capture the nature of a process upset.

TYPICAL APPLICATIONS

Continuous monitoring

Continuous moisture analysis is a valuable tool for quality assurance and process monitoring. As a quality assurance analyzer, the Model 5920 verifies that specified gas purity levels are maintained at on-site separation, bulk delivery and distribution system transfer points, and, ultimately, at points-of-use. The Model 5920 satisfies all the demands of continuous monitoring, principally low detection limit, high measurement accuracy, and internal verification.

Spot monitoring

The Model 5920 is the perfect analyzer for temporary monitoring applications for verifying installation, maintenance, or repair of gas distribution systems. Such temporary or spot testing makes excellent use of the unique combination of capabilities provided by the Model 5920: very fast response speed, especially to decreasing moisture concentrations for monitoring system dry-down; complete compatibility with oxygen, hydrogen, and inerts; rapid start-up response; and the ability to quickly change from one gas to another.

Cylinder gases

As cylinders are emptied, the drop in gas pressure causes an increase in moisture content in the remaining product. Consequently, many users change cylinders based on remaining pressure or weight. Because neither method directly measures moisture content, either expensive gas is wasted or impure gas enters the distribution system. The Model 5920's low sample flow requirement and multi-gas compatibility is ideal for assessing the purity of cylinder gases.



THE QUARTZ-CRYSTAL SENSOR

The heart of the 5920 analyzer is a quartz-crystal microbalance (QCM) sensor and analysis technique developed by AMETEK specifically for highly accurate moisture measurements. The sensor consists of a pair of electrodes that support the QCM sensor. When voltage is applied to the sensor, a very stable oscillation occurs.

The faces of the oscillator are covered with a hygroscopic polymer. As the amount of moisture sorbed onto the polymer varies, the mass of the QCM changes producing a corresponding change in the frequency of oscillation. These easily measurable changes have a direct relation to the moisture concentration of the sample gas.

PERFORMANCE SPECIFICATIONS

Compatible Gases: Inerts (He, Ar, Ne, Xe, Kr), H₂, O₂, N₂.
O₂ requires a special purifier. (Contact the factory to confirm compatibility with other gases.)

Range: 0 to 150 ppbv. Trend indication to 1000 ppbv

Limit of Detection: 1.0 ppbv nominal

Accuracy: ±1 ppbv or ±10% of the reading, whichever is greater

Sensitivity: Better than 1 ppbv

Response Time: 80% of a 25 ppb step change in either direction in less than 10 minutes

Inlet Pressure: 20 to 150 psig (138 to 1,035 kPa). Specified performance is obtained when the inlet gas pressure is maintained within ±2.5 psi (±17 kPa).

Exhaust Pressure: Atmospheric

Sample Flow Requirement: <0.5 slpm

Inlet Gas Temperature: 32° to 212°F (0° to 100°C). Optimal results are obtained when the inlet gas temperature is maintained at 140°F (60°C).

Outputs

Four-line by twenty-character LCD display
One self-powered 4 to 20 mA, into 100 to 500 ohm load analog output; can be configured for loop-powered operation
RS485 and RS232 serial ports

Alarms: System alarm, concentration alarm, and data valid
30 VAC or 60 VDC max, 50 VA or 1A max, resistive

Environmental Conditions

Ambient temperature range 50° to 86°F (10° to 30°C).
Optimal results are obtained when ambient is maintained within ±9°F (±5°C).
Relative humidity 90%, noncondensing
Pollution Degree 2
Maximum altitude 6560 feet (2000 meters)
Installation Category II
Indoor use only

Utility Requirements

100 - 132 VAC or 230 VAC ±10%, 47-63 Hz, 185W
Instrument Air: 80 to 100 psi (550 to 690 kPa),
-40°C dew point

Mounting Configuration: 19-inch rack

Dimensions (W x H x D): 19 x 7 x 20 in. (48 x 17.7 x 50.9 cm)

Net Weight: 35 lb (15.9 kg)

Approvals and Certifications

UL/CSA General Safety Requirements
Complies with all Relevant European Directives

One of a family of innovative process analyzer solutions from AMETEK Process Instruments. Specifications subject to change without notice.



CANADA
2876 Sunridge Way N.E.
Calgary, AB T1Y 7H9
Ph. 403-235-8400
Fax 403-248-3550

USA - Delaware
455 Corporate Blvd.
Newark, DE 19702
Ph. 302-456-4400
Fax 302-456-4444

USA - Pittsburgh
150 Freeport Road
Pittsburgh, PA 15238
Ph. 412-828-9040
Fax 412-826-0399

USA - Texas
9750 Whithorn Drive
Houston, TX 77095
Ph. 281-463-2820
Fax 281-463-2701

CHINA
Ph. 8621 6426 7049
Fax 8621 6426 7054

FRANCE
Ph. 33 1 30 68 69 20
Fax 33 1 30 68 69 29

GERMANY
Ph. 49 21 59 91 36 0
Fax 49 21 59 91 36 80

MIDDLE EAST - Dubai
Ph. 971-4-881 2052
Fax 971-4-881 2053



www.ametekpi.com
© 2002, by AMETEK, Inc. All rights reserved.

