



ANALYZER SOLUTIONS FOR YOUR PROCESS!

ta5000F FID Gas Analyzer Specifications

Model designation and detection limit specifications

Every ta5000F includes: an on-board electronic pressure regulator, multipoint diaphragm valve, proven chromatography, and Flame Ionization Detector (FID). Lower detection limits may vary depending on application. Contact AMETEK for information about your specific application. Not all models and applications are listed below.

Applications	Lower Detection Limit	Analysis Time
Nitrogen	4 ppb CO ₂ ; 3 ppb CH ₄ ; 7 ppb NMHC	10 minutes
Argon	5 ppb CO ₂ ; 5 ppb CH ₄ ; 8 ppb NMHC	10 minutes
Helium	5 ppb CO ₂ ; 5 ppb CH ₄ ; 8 ppb NMHC	10 minutes
Oxygen	7 ppb CO ₂ ; 6 ppb CH ₄ ; 10 ppb NMHC	10 minutes
Hydrogen	5 ppb CO ₂ ; 5 ppb CH ₄ ; 8 ppb NMHC	10 minutes

Performance

Precision	±1 x LDL or ± 2% of reading, which ever is greater
Accuracy	±1 x LDL or ± 2% of reading, which ever is greater
Range	0 to 5 ppm (Higher is available as an option)
Response Time	2 to 10 minutes to 99% response (varies with application) Response time is independent of sample concentration.
Ambient Operating Temperature	50° to 90°F (16° to 32°C)
Sample Compatibility	Specific models available for various applications
Resolution, Display	0.1 ppb
Resolution, Communication Ports	0.01 ppb

Carrier Gas Supplies (On-Line Installation)

Inlet Pressure Range	70 to 90 psig (4.8 to 6.1 bar)
Inlet Pressure Stability	± 2%, regulator required
Return Pressure	Atmospheric vent is optimal, ± 0.5 psig maximum
Flow Consumption	50 cc/min minimum, bypass at 50 cc/min
Temperature	60° to 100°F (16° to 38°C), optimum when maintained ± 2°C
Maximum Impurity Levels	Varies by application, inlet purifier may be required

Support Gases

Carrier Gas	Nitrogen (typical)
Carrier Gas Purity	99.995% (external purifier may be required)
FID Air Purity	< 1ppm hydrocarbons, dewpoint < -40°C
FID Hydrogen Fuel Purity	Hydrocarbons, CO, CO ₂ <1ppm

ta5000F FID Gas Analyzer

Specifications

Gas Ports

Sample Inlet	1/16-inch VICI compression
Carrier	1/16-inch VICI compression
Actuator Gas	1/8-inch VICI compression
FID H ₂	1/16-inch VICI compression
FID Air	1/16-inch VICI compression
Sample Vent	1/16-inch VICI compression
Aux	1/16-inch VICI compression
FID Shut-Off	1/8-inch VICI compression

Sample Gas

Inlet Fitting	1/16-inch VICI compression fitting
Flow Rate	20 - 100 sccm minimum
Inlet Pressure Stability	± 2%, UHP regulator required
Vent Pressure	Atmospheric pressure vent is optimal, ± 0.5 psig maximum

Calibration Gas

Inlet Fitting	Sample Gas Inlet (1/16-inch VICI compression fitting)
Cylinder Concentration	Depends on application
Blender Recommended	AMETEK Trace Analytical MGB1000 Micro Gas Blender

Chassis

Dimensions	7" H x 16.8" W x 26.5" D (18 cm x 43 cm x 67 cm)
Weight	35 lb. (15.9 kg)
Power	100 - 120 VAC, 50/60 Hz; 200 - 240 VAC, 50/60 Hz

One of a family of innovative process analyzer solutions from AMETEK Process Instruments. Specifications subject to change without notice.

USA - Pennsylvania
150 Freeport Road
Pittsburgh, PA 15238
Ph. 412-828-9040
Fax 412-826-0399

**MANUFACTURING
LOCATIONS**



CANADA
2876 Sunridge Way N.E.
Calgary, AB T1Y 7H9
Ph. 403-235-8400
Fax 403-248-3550

USA - Delaware
455 Corporate Blvd.
Newark, DE 19702
Ph. 302-456-4400
Fax 302-456-4444

USA - Oklahoma
2001 N. Indianwood Ave.
Broken Arrow, OK 74012
Ph. 918-250-7200
Fax 918-459-0165

AMETEK[®]
PROCESS INSTRUMENTS
www.ametekpi.com

© 2004, by AMETEK, Inc. All rights reserved.
spec ta5000F(10/04)

**SUPPORT
LOCATIONS**

USA - Texas
Ph. 281-463-2820
Fax 281-463-2701

CHINA - Beijing
Ph. 86-10-85262111
Fax 86-10-85262141

CHINA - Shanghai
Ph. 86 21 6426 7049
Fax 86 21 6426 7054

FRANCE
Ph. 33 1 30 68 69 20
Fax 33 1 30 68 69 29

GERMANY
Ph. 49 21 59 91 36 0
Fax 49 21 59 91 36 80

MIDDLE EAST - Dubai
Ph. 971-4-881 2052
Fax 971-4-881 2053

SINGAPORE
Ph. 65-6484-2388
Fax 65-6481-6588